



MINIPULSE 201 DP

- Allows pulse curves to be activated for aluminum, mild steel and CuSi3;
- Waveform control for greater arc stability, even at low currents;
- Digital control of all welding parameters;
- Optional: trolley and water cooling unit;
- Equipped with voltage and current temperature sensors for high protection;
- For 5kg coils.



Model	MINIPULSE 201 DP					
Supply voltage (V)	1~110V±10% 50/60Hz			1~230V±10% 50/60Hz		
Nominal input capacity	MIG	MMA	TIG	MIG	MMA	TIG
Input current range	4.0	3.5	4.3	6.2	6.2	4.2
Effective current (A)	33	28	31	27	30	20
Duty cycle (40°C 10 min)	20	15	17	15	15	12
Welding current range	30% 140A 60% 110A 100% 85A	30% 110A 60% 80A 100% 65A	40% 150A 60% 125A 100% 95A	30% 200A 60% 145A 100% 110A	25% 200A 60% 130A 100% 100A	35% 200A 60% 155A 100% 120A
No voltage (V)	40A-140A	10A-110A	10A-150A	40A-200A	10A-200A	10A-200A
Weight (Kg)	70					
Dimensions (mm)	12					
Insulation class	510x215x400					
Protection class	H					
Cooling	IP23					
Efficiency	AF					
Wire diameter (mm)	80%					
	Fe:0.6/0.8/0.9/1.0 Ss:0.8/0.9/1.0 Flux:0.6/0.8/0.9/1.0					