



MULTI 300

Optional: Spool Gun Torch



Drag motor – 4 rolls

1.250€ + IVA



Characteristics:

- ⇒ Integrated wire feeder, equipped with gas cylinder support
- ⇒ MIG / MMA / Lift-TIG modes
- ⇒ MMA mode with VRD control
- ⇒ With reverse polarity
- ⇒ In MMA mode can be used as TIG Lift-Arc.
- ⇒ With protections against overcurrent, overheating and under voltage
- ⇒ Current and voltage in a separated digital display
- ⇒ 3PROOF function (moisture proof, salt spray proof and corrosion proof)
- ⇒ Can be used for industrial applications

Model	MULTI 300		
Power supply voltage (V)	3 Phase 380 V, $\pm 15\%$		
Frequency (Hz)	50/60		
	MIG	MMA	TIG
Rated input power (kW)	10.2	11.3	7.8
Rated input current (A)	17	18.8	12.7
Duty cycle (%)	40% - 300A		
	100% - 232A		
No-load voltage (V)	60		
Welding current range (A)	50-300	25-300	-
Welding voltage range (V)	14-30	-	-
Efficiency (%)	≥ 85		
Power factor	0.93		
Protection class	IP 23		
Insulation class	H		
Cooling	AF		
Wire diameter (mm)	0.8/1.0/1.2	1.6~5.0	-
Weight (Kg)	52		
Gross weight (Kg)	58		
Packing dimensions (CxLxA)	900 x 440 x 790 mm		