



Multi XL 251 LCD

- LCD display: 4.3 inches in color;
- Arc Controller: control of the shape of the arc, for greater arc stability, even at low currents;
- Protection: Equipped with temperature, voltage and current sensors for high protection;
- Optional Spool Gun.



Model	Multi XL 251 LCD					
Power supply voltage (V)	90VAC~275VAC 1~110/120/130±10%			90VAC~275VAC 1~220/230/240±10%		
Frequency	50/60 Hz			50/60 Hz		
	MIG	MMA	TIG	MIG	MMA	TIG
Power (KW)	4.1	3.3	3.2	7.9	8.9	6.3
Current (A)	34	27	26	35	40	28
Effective current (A)	26	21	20	27	31	22
Duty cycle (40°C 10 Min)	60% 150A	60% 110A	60% 150A	60% 250A	60% 250A	60% 250A
	100% 120A	100% 85A	100% 120A	100% 195A	100% 195A	100% 195A
Welding current range (A)	40~150	10~110	10~150	40~250	10~250	10~250
No-load voltage	68					
Weight (kg)	25.5 kg					
Diameter (mm)	Fe: 0.6/0.9/1.0/1.2 Ss:0.8/0.9/1.0/1.2 Flux-Cored: 0.6/0.8/0.9/1.0/1.2					
Dimensions	630 X 240 X 445					
Insulation class	H					
Protection class (mm)	IP23					
Cooling	AF					
Power	0.99					