



MOBIL 403 SW H2O

Characteristics

Option to work
with a second
separate feeder



**Optional
feeder**



- Digital display with welding parameters;
- Arc stability even at low current;
- Equipped with 4R H2O wire feeder (optional);
- Equipped with MIG torch and cable kit
- Equipped with temperature, voltage and current sensors for high protection;



5m and 10m cable available 10 M

Model	MOBIL 403 SW H2O		
Supply voltage (V)	3~400±10%		
Input current (A)	MIG: 30.9	MMA: 32.7	TIG: 24
Input power (KW)	MIG: 9.6	MMA: 10.1	TIG: 7.4
Welding voltage (V)	MIG: 15 – 34	MMA: 20.4 – 36	TIG: 10.4 – 26
Welding current (A)	MIG: 20 – 400	MMA: 10 – 400	TIG: 10 – 400
No-load voltage (V)	72		
Duty cycle (40°C)	60% 400A 100% 310A		
Diameter (mm)	Fe: 0.8/0.9/1.0/1.2/1.6 Ss: 0.9/1.0/1.2/1.6 AL: 1.0/1.2/1.6 Flu.Fe: 0.9/1.0/1.2/1.6		
Protection class	IP21S		
Insulation class	H		
Weight (Kg)	76		
Dimensions (mm)	750 x 300 x 810		